

## MITREBOND ACTIVATOR

Page: 1

Compilation date: 08/02/2016

Revision date: 03/08/2017

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: MITREBOND ACTIVATOR

Product code: MBAERO

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

#### 1.3. Details of the supplier of the safety data sheet

Company name: Unika Color Products Ltd

- Unika House
- New York Way
- New York Industrial Park
- Newcastle upon Tyne
- NE27 0QF
- United Kingdom
- Tel: +44 (0) 191-259-0033
- Fax: +44 (0) 191-257-4525
- Email: technical@unika.co.uk

# 1.4. Emergency telephone number

## Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP:	Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -:
	H229
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin
	irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting
	effects.

#### 2.2. Label elements

Label elements:	
Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame

## MITREBOND ACTIVATOR

Page: 2

GHS07: Exclamation mark

GHS09: Environmental



Signal words:	Danger
Precautionary statements:	P102: Keep out of reach of children.
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P211: Do not spray on an open flame or other ignition source.
	P251: Do not pierce or burn, even after use.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+352: IF ON SKIN: Wash with plenty of water/.
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive dust-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

## Hazardous ingredients:

PROPANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%
HEPTANE				

2	05-563-8	142-82-5	-	Flam. Liq. 2: H225; Asp. Tox. 1: H304;	10-30%
				Skin Irrit. 2: H315; STOT SE 3: H336;	
				Aquatic Acute 1: H400; Aquatic Chronic	
				1: H410	

#### BUTANE

203-448-7	106-97-8	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		workplace exposure limit.		

## MITREBOND ACTIVATOR

## **Page:** 3

	75-28-5	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	1-10%
		workplace exposure limit.		
N,N-DIMETHYL	-P-TOLUIDIN	١E		
202-805-4	99-97-8	-	Acute Tox. 3: H331; Acute Tox. 3: H311;	<1%
			Acute Tox. 3: H301; STOT RE 2: H373;	
			Aquatic Chronic 3: H412	
ion 4: First ai	id measure	5		
. Description	of first aid m	easures		
			nd footwear immediately unless stuck to skin.	
· · · ·			g water for 10 minutes or longer if substance i	s still
		on skin.		o otin
1	Eve contact:	Bathe the eye with running water for	15 minutes. Consult a doctor.	
	-	Do not induce vomiting. Consult a do		
		Move to fresh air in case of accident		
. Most import		is and effects, both acute and delay	•	
		There may be irritation and redness		
<b>Eye contact:</b> There may be irritation and redness. The eyes may water profusely.				
<b>Ingestion:</b> There may be soreness and redness of the mouth and throat.				
	Inhalation:	-	with a feeling of tightness in the chest. Exposu	ire may
cause coughing or wheezing.				
laved / immed	liate effects:	Immediate effects can be expected a	-	
	f any immedi	ate medical attention and special tr	reatment needed	
8. Indication of		Eye bathing equipment should be av		
8. Indication of	al treatment:	Eye bathing equipment should be av		
3. Indication of ediate / specia	al treatment: ghting meas	Eye bathing equipment should be av		
3. Indication of ediate / specia ion 5: Fire-fig I. Extinguishin	al treatment: ghting meas ng media	Eye bathing equipment should be av	vailable on the premises.	
3. Indication of ediate / specia ion 5: Fire-fig I. Extinguishin	al treatment: ghting meas ng media	Eye bathing equipment should be av sures Suitable extinguishing media for the		Dray
8. Indication of ediate / specia ion 5: Fire-fig I. Extinguishin Extinguis	al treatment: ghting meas ng media shing media:	Eye bathing equipment should be av sures Suitable extinguishing media for the to cool containers.	vailable on the premises.	oray
8. Indication of ediate / specia ion 5: Fire-fig . Extinguishin Extinguis 2. Special haza	al treatment: ghting meas ng media shing media: ards arising f	Eye bathing equipment should be average of the substance or mixture	vailable on the premises.	-
8. Indication of ediate / specia ion 5: Fire-fig . Extinguishin Extinguis 2. Special haza	al treatment: ghting meas ng media shing media: ards arising f	Eye bathing equipment should be average sources Suitable extinguishing media for the to cool containers. From the substance or mixture Extremely flammable. In combustion	vailable on the premises. surrounding fire should be used. Use water sponter states to the state states to the sta	ır
8. Indication of ediate / specia ion 5: Fire-fig . Extinguishin Extinguis 2. Special haza	al treatment: ghting meas ng media shing media: ards arising f	Eye bathing equipment should be average sources Suitable extinguishing media for the to cool containers. From the substance or mixture Extremely flammable. In combustion	vailable on the premises.	ır
8. Indication of ediate / specia ion 5: Fire-fig . Extinguishin Extinguis 2. Special haza	al treatment: ghting meas ng media shing media: ards arising f ure hazards:	Eye bathing equipment should be average sources Suitable extinguishing media for the to cool containers. From the substance or mixture Extremely flammable. In combustion	vailable on the premises. surrounding fire should be used. Use water sponter states to the state states to the sta	ır
<ol> <li>Indication of ediate / specialion 5: Fire-figlering</li> <li>Extinguishin Extinguis</li> <li>Special haza Exposu</li> <li>Advice for figlering</li> </ol>	al treatment: ghting meas ng media shing media: ards arising f ure hazards: re-fighters	Eye bathing equipment should be average sources Suitable extinguishing media for the to cool containers. From the substance or mixture Extremely flammable. In combustion mixture. Vapour may travel consider	vailable on the premises. surrounding fire should be used. Use water sponter states to the state states to the sta	ır ack.

[cont...]

#### MITREBOND ACTIVATOR

#### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Hazardous ingredients:

#### PROPANE

#### Workplace exposure limits:

# **Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1800 mg/m3	7200 mg/m3	-	-

## MITREBOND ACTIVATOR

HEPTANE				
UK	2100 mg/m3	8400 mg/m3	-	-
BUTANE				
UK	1450 mg/m3	1810 mg/m3	-	-
ISOBUTANE				
UK	2400 mg/m3	9600 mg/m3	-	-
NEL /PNEC Value				
NEL/PNEC Value	25			
DN	EL / PNEC No data availab	le.		

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical	
	equipment are not a source of ignition.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
Environmental:	Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State:	Aerosol
Colour:	Colourless
Odour:	Characteristic odour
	10

pH: No data available.

Boiling point/range°C: -40

Flash point°C: -60

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### MITREBOND ACTIVATOR

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

#### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### HEPTANE

IVN MUS LD50	222	mg/kg
--------------	-----	-------

#### N,N-DIMETHYL-P-TOLUIDINE

IPR	MUS	LD50	212	mg/kg
-----	-----	------	-----	-------

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

## MITREBOND ACTIVATOR

#### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

#### Section 13: Disposal considerations

13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

#### Section 14: Transport information

## 14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

#### 14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

#### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

## MITREBOND ACTIVATOR

## Section 16: Other information

Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	
	2015/830.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.	
	H222: Extremely flammable aerosol.	
	H225: Highly flammable liquid and vapour.	
	H229: Pressurised container: May burst if heated	
	H301: Toxic if swallowed.	
	H304: May be fatal if swallowed and enters airways.	
	H311: Toxic in contact with skin.	
	H315: Causes skin irritation.	
	H331: Toxic if inhaled.	
	H336: May cause drowsiness or dizziness.	
	H373: May cause damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through</or>	
	prolonged or repeated exposure <state conclusively="" exposure="" if="" is="" it="" of="" proven="" route="" th="" that<=""></state>	
	no other routes of exposure cause the hazard>.	
	H400: Very toxic to aquatic life.	
	H410: Very toxic to aquatic life with long lasting effects.	
	H411: Toxic to aquatic life with long lasting effects.	
	H412: Harmful to aquatic life with long lasting effects.	
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive	
	and shall be used only as a guide. This company shall not be held liable for any	
	damage resulting from handling or from contact with the above product.	
	damage resulting from handling or from contact with the above product.	