

Date: 04 August 2011

Information Sheet No.: TDS01642

EVO-STIK STICKS LIKE CLEAR ADHESIVE

A HIGH STRENGTH, ONE COMPONENT, HYBRID POLYMER ADHESIVE

Evo-Stik Sticks Like Clear is a high performance, one component, moisture curing adhesive that offers excellent initial grab and a high strength bond. It will bond most surfaces even if both are impervious and can be applied to damp or wet surfaces. Evo-Stik Sticks Like Clear is low odour and a truly versatile adhesive suitable for interior and exterior use. When fully cured the product may be over painted with most types of paints. Before using this product refer to the relevant Health & Safety Data Sheet.

Features

- Clear formulation
- Bonds to most surfaces including wood, concrete, brick, plaster, glass, ceramics, metals, rigid pvc, grp, insulation boards and foam polystyrene.
- Excellent adhesion and initial grab.
- Suitable for interior or exterior use.
- Wide service temperature range
- Can be overpainted

Product Characteristics

Colour	Clear
Composition	Moisture curing Hybrid Polymer based system
Specific Gravity	1.05
Product Code	663824 C20 Cartridges x 12
Shelf life/storage	12 months when stored in the original unopened containers. Store under dry conditions between 5°C and 25°C and out of direct sunlight. Protect from frost.

Typical Performance Data (approx.)

Drying Time:	<i>Touch Dry:</i> 30 - 40 minutes <i>Cure Time:</i> 24 hours (Dependent on bead size and substrates being bonded)
Shore A hardness	25 - 29
Tensile strength	> 22MPa (at 50% extension)
Service Temperature	- 40°C to +100°C

Paintability Cured product may be over-painted with most types of paints excluding alkyd resin paints

Coverage 10 metres of 6mm diameter bead per C20 cartridge.

Precautions in Use

Will not bond Polyethylene, Polypropylene or Teflon. It should not be used on surfaces contaminated with bitumen. Not suitable for use on aquaria or for fixing mirrors.

Directions for use

IMPORTANT

Before using Evo-Stik Sticks Like Clear Adhesive refer to the relevant Health & Safety Data Sheet. Available at www.bostik.co.uk named as the code above.

1. Surfaces must be clean and free from dust, oil, grease and any loose material. Damp surfaces must be checked for weak or loose matter on the surface that the damp might hide.
2. Cut off the dome at the top of the cartridge taking care not to damage the thread. Cut the nozzle to the required diameter and screw onto the cartridge.
3. Insert the cartridge into a cartridge gun.
4. Apply adhesive in continuous beads to one of the surfaces, then immediately press the two materials firmly together with a slight twisting action.
5. For larger surfaces apply a continuous bead around the edge approx. 1 cm from the side and apply further beads at approximately 30cm intervals.
6. Heavy objects may require temporary support until the adhesive sets.

Date: 04 August 2011

Information Sheet No.: TDS01642

Cleaning

Clean equipment and remove excess adhesive immediately using a cloth and white spirit.

Cured product requires mechanical removal.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Evo-Stik Sticks Like Clear Adhesive

Sales & Technical contacts at Bostik

	Telephone	Facsimile	Email addresses
Sales	0844 371 1192	01785 241818	customer.service@bostik.com
Technical advice	0844 371 1197	01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) sheets	01785 272625	01785 212962	stafford.gatehouse@bostik.com

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.