

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 05.04.2017

Version number 14

Revision: 06.10.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** **Osmo TopOil**

**Article number:** 3028 Clear Satin, 3037 White, 3038 Terra; 3039 Graphite, 3058 Clear Matt, 3061 Acacia, 3068 Natural

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**advised against** No further relevant information available.

#### Application of the substance / the mixture

Paint  
 Coating compound/ Surface coating/ paint

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
 Affhüppen Esch 12  
 D-48231 Warendorf

#### Further information obtainable from:

Product safety department  
 Phone: +49 (0) 251 / 692 - 188  
 Fax: +49 (0) 251 / 692 - 462  
 e-mail: helmut.starp@osmo.de

#### 1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to

**Regulation (EC) No 1272/2008** The product is not classified according to the CLP regulation.

#### 2.2 Label elements

##### Labelling according to Regulation

**(EC) No 1272/2008** Void

**Hazard pictograms** Void

**Signal word** Void

**Hazard statements** Void

##### Precautionary statements

Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P271 Use only outdoors or in a well-ventilated area.

P262 Do not get in eyes, on skin, or on clothing.

##### Additional information:

Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Safety data sheet available on request.

(Contd. on page 2)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 05.04.2017

Version number 14

Revision: 06.10.2016


**Trade name: Osmo TopOil**

(Contd. of page 1)

**2.3 Other hazards**

Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

EC number: 918-481-9	aliphatic hydrocarbons, C10-C13	 Asp. Tox. 1, H304	25-50%
Index number: 649-327-00-6			
Reg.nr.: 01-2119457273-39			

**Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:**

If swallowed, seek medical advice immediately and show this container or label.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable****extinguishing agents:** Water with full jet

(Contd. on page 3)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 05.04.2017

Version number 14

Revision: 06.10.2016

**Trade name: Osmo TopOil**

(Contd. of page 2)

**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters****Protective equipment:**

Mouth respiratory protective device.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Ensure adequate ventilation  
Keep away from ignition sources.**6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**Warm water and cleansing agent  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).**6.4 Reference to other sections**See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.**SECTION 7: Handling and storage****7.1 Precautions for safe handling**Keep away from heat and direct sunlight.  
Use only in well ventilated areas.  
Keep receptacles tightly sealed.  
Prevent formation of aerosols.**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**Store only in the original receptacle.  
Store in a cool location.**Information about storage in one common storage facility:**Do not store together with alkalis (caustic solutions).  
Do not store together with oxidising and acidic materials.**Further information about storage conditions:**Store in cool, dry conditions in well sealed receptacles.  
Keep container tightly sealed.

(Contd. on page 4)

**Trade name: Osmo TopOil**

(Contd. of page 3)

7.3 *Specific end use(s)*

No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

**Additional information about design of technical facilities:**

No further data; see item 7.

#### **8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m <sup>3</sup> , 150 ppm ppm
	Source: UK SIA

**Additional information:**

The lists valid during the making were used as basis.

#### **8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing  
Keep away from foodstuffs, beverages and feed.  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Do not carry product impregnated cleaning cloths in trouser pockets.

**Respiratory protection:**

Not necessary if room is well-ventilated.  
Use suitable respiratory protective device only when aerosol or mist is formed.  
Short term filter device:  
Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 °C)).

**Protection of hands:**

Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
To avoid skin problems reduce the wearing of gloves to the required minimum.

**Material of gloves**

Nitrile rubber, NBR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

(Contd. on page 5)

**Trade name: Osmo TopOil**

(Contd. of page 4)

*For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:*

Nitrile rubber, NBR

*As protection from splashes gloves made of the following materials are suitable:*

Recommended thickness of the material:  $\geq 0.1$  mm

*Eye protection:*

Goggles recommended during refilling

*Body protection:*

Protective work clothing

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

**Form:** Viscous

**Colour:** According to product specification

**Odour:** Mild

**Change in condition**

**Melting point/freezing point:** Undetermined.

**Initial boiling point and boiling range:**  $> 180$  °C (DIN 51751)

**Flash point:**  $> 61$  °C (DIN EN ISO 2719)

**Ignition temperature:** 240 °C

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product does not present an explosion hazard.

**Explosion limits:**

**Lower:** 0.6 Vol %

**Upper:** 7.0 Vol %

**Vapour pressure:** Not determined.

**Density at 20 °C:** 0.92-0.98 g/cm<sup>3</sup> (DIN 51757)

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Viscosity:**

**Dynamic:** Not determined.

**Kinematic at 20 °C:** 40-70 s (DIN EN ISO 2431/4 mm)

**Solvent content:**

**VOC (EC)** Not applicable.

(Contd. on page 6)

**Trade name: Osmo TopOil**

(Contd. of page 5)

**9.2 Other information**

No further relevant information available.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No further relevant information available.

**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

**10.4 Conditions to avoid**

No further relevant information available.

**10.5 Incompatible materials:**

No further relevant information available.

**10.6 Hazardous decomposition products:**Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****aliphatic hydrocarbons, C10-C13**

Oral LD50 &gt; 5000 mg/kg (rat) (OECD 401)

Dermal LD50 &gt; 5000 mg/kg (rat) (OECD 402)

Inhalative LC50 / 4h 21 mg/l (rat) (OECD 403)

**Primary irritant effect:****Skin corrosion/irritation**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**Serious eye damage/irritation**

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

**Carcinogenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

(Contd. on page 7)

**Trade name: Osmo TopOil**

(Contd. of page 6)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Aquatic toxicity:

##### aliphatic hydrocarbons, C10-C13

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abbaubar)

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

##### Additional ecological information:

**General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

##### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### European waste catalogue

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10	packaging containing residues of or contaminated by dangerous substances

##### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

**Recommended cleansing agents:** Solvent naphtha

### SECTION 14: Transport information

#### 14.1 UN-Number

ADR, ADN, IMDG, IATA

Void

(Contd. on page 8)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 05.04.2017

Version number 14

Revision: 06.10.2016

**Trade name: Osmo TopOil**

(Contd. of page 7)

<b>14.2 UN proper shipping name</b> ADR, ADN, IMDG, IATA	Void
<b>14.3 Transport hazard class(es)</b> ADR, ADN, IMDG, IATA Class	Void
<b>14.4 Packing group</b> ADR, IMDG, IATA	Void
<b>14.5 Environmental hazards:</b> Marine pollutant:	No
<b>14.6 Special precautions for user</b>	Not applicable.
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
<b>UN "Model Regulation":</b>	Void

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:****GISBAU-Code** GISCODE: Ö60**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

<b>Relevant phrases</b>	H304 May be fatal if swallowed and enters airways.
<b>Department issuing SDS:</b>	product safety department
<b>Contact:</b>	Hr. Dr. Starp
<b>Abbreviations and acronyms:</b>	ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)



**Material Safety Data Sheets**  
*according to 1907/2006/EC, Article 31*



Printing date 05.04.2017

Version number 14

Revision: 06.10.2016

**Trade name: Osmo TopOil**

vPvB: very Persistent and very Bioaccumulative  
Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. of page 8)

