



Construction	
Construction	Stile and rail
Construction material	Dowel and glue construction
Country of origin	Various
Lock block additional information	A lock block is not necessary as this is a solid construction. The lock can be fitted in any location on either side
Glazing fixing method	Beading and Pinned
Glazing style	Clear

Edging Information	
	Maximum trim
Top	3 mm
Bottom	3 mm
Each side	3 mm

### Fitting and finishing

Please refer to door instructions for all fitting information. This door has a particleboard core which may be exposed if rebated. The use of the pine door pair maker is therefore recommended. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door. This door is suitable for finishing with: paint (Including the beading for glazing which must be primed and undercoated in order for the paint to adhere properly).

Ready for painting

Supplied with toughened clear glass

Glazing certificate available

Dimensions							
Product code	Product height	Product width	Product thickness	Product weight	Top rail	Glazing thickness	Bottom rail
DGT1940 <b>NEW</b>	6'6" / 1981mm	2'3" / 686mm	35mm	19.997kg	117mm	4mm	185mm
DGT1960 <b>NEW</b>	6'6" / 1981mm	2'6" / 762mm	35mm	21.997kg	117mm	4mm	185mm
DGT1970 <b>NEW</b>	6'6" / 1981mm	2'9" / 838mm	35mm	23.997kg	117mm	4mm	185mm

#### Key information

All sizes subject to standard industry tolerances

**M** = Part M - Mobility and access\*

**L** = Part L - Warmth & insulation suitable for new build\*

**L** = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

**FD30/60/120** = Certified fire door\*

**F** = Forest Stewardship Council (FSC®)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)\*

**UK** = UK Manufactured

† = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards