

# SDH3689 Quick-Step Livyn canyon beige oak



**Key**  
**F** = FSC®  
**P** = PEFC™  
**UK** = UK Manufactured  
**†** = Subject to availability

| Associated products                            |                            |
|--|----------------------------|
| SelitBloc® Vinyl underlay 1.18m x 8.5m x 1.5mm | SDH0926                    |
| White Oak Scotia (L2.4m)                       | <b>NEW UK P</b><br>SDH6750 |
| Clear edge T-Bar                               | SDH4120                    |
| Chrome pipe rose Pack of 4                     | SDH0895                    |
| Vinyl Flooring Roller                          | SDH9013                    |

| Construction  |                        |
|---------------|------------------------|
| Surface layer | 0.3mm Clear Wear Layer |
| Substrate     | 4.5mm PVC              |

| Technical Information                 |  |
|---------------------------------------|--|
| Range                                 | Vinyl Flooring   |
| Flooring format                       | Single plank   |
| Locking system                        | Click Fit Glueless   |
| Finish                                | Textured   |
| Glue / resin                          | Internal recipe - cannot be supplied to customer           |
| Moisture content                      | N/A  |
| Impact resistance                     | EN 13329 - Class IC2                                       |
| Abrasion class                        | AC4 - medium commercial use                                |
| Light fastness                        | EN 13329 Blue Scale class 6                                |
| Reaction to fire                      | Class Efi - EN14041  |
| Level of use of according to EN13329* | Class 23 (Heavy Domestic)<br>Class 32 (General Commercial) |
| Thermal conductivity                  | 0.015 W/mK   |
| Effect of castor chairs               | EN 13329- 25,000 cycles no change                          |

| Technical Information           |   |
|---------------------------------|---|
| Resistance to staining          | EN 438 Group 1 + 2 Grade 5 & Group 3 Grade 4<br>EN 13329 - Group 1 + 2 (Grade 5) & Group 3 (Grade 4)  |
| Slip resistance                 | EN 13893 Technical Class DS   |
| Formaldehyde emission           | E1 - < 0.025 PPM - EN 717-1   |
| Laying detail                   | Must be laid as a floating floor (see instructions)   |
| Suitable for underfloor heating | Yes - Electric and radiant if installed as per the instructions (note must not exceed 27 degrees)   |
| Fitting instructions            | Underfloor heating systems (water / electrical) should be built into a layer of screed when used in conjunction with Quick-Step Livyn flooring and kept at a constant room temperature of 18°C (64°F) during installation and for 48h after installation. Once installed the floor surface temperature must not go above a maximum of 27°C (80°C). Separate rooms or rooms with different underfloor heating systems should be installed with a transition profile. |

| Dimensions & packaging      |                           |
|-----------------------------|---------------------------|
| Product dimensions metric   | W187mm xL1,250mm x D4.5mm |
| Product weight              | 17.1kg                    |
| Quantity                    | 9                         |
| Product packed dimension    | H42mm x W1,278mm x D202mm |
| Volume coverage / pack size | 2.105 m/sq                |



Dimensions & packaging

|                       |        |
|-----------------------|--------|
| Product packed weight | 17.5kg |
|-----------------------|--------|

