

Grey Oak Effect Square Edged Laminate 22mm



Technical Information	
Material	Chipboard
Worktop profile	Square edged
Moisture resistance grade	P2
Worktop process	CPL
Maximum overhang	300 mm
Accreditation general	BS 6222:1999 part 3 BS EN 312 (Board spec test - Domestic use compliance)

Dimensions & packaging	
Product dimensions metric	L3,000mm x D616mm x T22mm
Product weight	27kg
Product packed dimension	H24mm x W3,050mm x D616mm
Product packed weight	27kg

Care & Installation	
Care and maintenance	<p>For general cleaning, use a damp cloth and a mild detergent or non-abrasive cleaner diluted in warm water</p> <p>Abrasive scouring powders, creams and polishes should be avoided. Potentially persistent stains should be removed immediately. Buff the surface after cleaning with a soft cloth</p> <p>Wipe spilt liquid away from the worktop joints and cut-outs immediately</p> <p>When applying the edging please ensure that it is lined up with the top of the worktop and overhangs at the bottom</p> <p>Trim the edging at the bottom so that the trimmed edge is out of sight</p>

Additional information
<p>Support rails are required with certain cabinet configurations. Please check the support bar application document</p> <p>Slim worktop bolt - GIR0029 must be used when fitting the 22mm laminate worktop. This has a thinner profile to fit the worktop</p>

Products	
3m length	NEW UK F WHT5260
2.4m breakfast bar (950mm deep)	UK F WHT5285
5m Edging strip	UK WHT5295
Upstand 3m x 70mm x 20mm	UK P WKP0292
Backboard 3m x 600mm x 7mm	UK WKP0297
Backboard 1m x 750mm x 7mm	UK WKP0298
Square profile sealer strip x 2	UK WTC9410
Jointing compound	UK WOR9033
Laminate sample	UK F
Slim Worktop Bolt	GIR0029



Key information

F = Forest Stewardship Council (FSC®)

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)

UK = UK Manufactured



Version : 10.D.L

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.