

## 6 Panel Grained fire doors



Construction	
Construction material	Constructed using softwood timber stile and rail frame
Material core	Routed Flaxboard Core
Core material thickness	38 mm

Edging Information		
	Lipping dimensions	Maximum trim
Top		0 mm
Bottom		6 mm
Each side		4 mm
Edging additional information	An equal amount of timber should be removed from each side & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised and that the door when fitted complies with the fire certificate.	

### Fitting and finishing

Please refer to door instructions for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door. All fire doors must be fitted in accordance with the fire certificate.



Dimensions									
Product code	Product height	Product width	Product thickness	Product weight	Fire rating	Building regulations	Stile	Top rail	Bottom rail
DIF0531 <b>P UK</b>	6'6" / 1981mm	2'0" / 610mm	44mm	22.996kg	<b>FD30</b>	<b>E</b>	107mm	94mm	171mm
DIF0541 <b>P UK</b>	6'6" / 1981mm	2'3" / 686mm	44mm	25.816kg	<b>FD30</b>	<b>E</b>	94mm	94mm	171mm
DIF0561 <b>P UK</b>	6'6" / 1981mm	2'6" / 762mm	44mm	28.896kg	<b>FD30</b>	<b>E</b>	107mm	94mm	171mm
DIF0571 <b>P UK</b>	6'6" / 1981mm	2'9" / 838mm	44mm	31.696kg	<b>FD30</b>	<b>E M</b>	119mm	94mm	191mm
DIF0580 <b>P UK</b>	6'8" / 2032mm	2'8" / 813mm	44mm	31.496kg	<b>FD30</b>	<b>E M</b>	106.5mm	109mm	209mm
DIF0920 <b>P UK</b>	2040mm	526mm	44mm	20.384kg	<b>FD30</b>	<b>E</b>	112mm	109mm	216mm
DIF0930 <b>P UK</b>	2040mm	626mm	44mm	24.396kg	<b>FD30</b>	<b>E</b>	115mm	109mm	216mm
DIF0940 <b>P UK</b>	2040mm	726mm	44mm	28.296kg	<b>FD30</b>	<b>E</b>	114mm	109mm	216mm
DIF0960 <b>P UK</b>	2040mm	826mm	44mm	32.196kg	<b>FD30</b>	<b>E M</b>	113mm	109mm	216mm
DIF0970 <b>P UK</b>	2040mm	926mm	44mm	36.096kg	<b>FD30</b>	<b>E M</b>	112mm	109mm	216mm
DIF5440 <b>P UK</b>	6'6" / 1981mm	2'3" / 686mm	35mm	21.132kg	<b>FD30</b>	<b>E</b>	94mm	94mm	171mm
DIF5460 <b>P UK</b>	6'6" / 1981mm	2'6" / 762mm	35mm	23.432kg	<b>FD30</b>	<b>E</b>	107mm	94mm	171mm
DIF5470 <b>P UK</b>	6'6" / 1981mm	2'9" / 838mm	35mm	25.832kg	<b>FD30</b>	<b>E M</b>	119mm	94mm	191mm
DIF5480 <b>P UK</b>	6'8" / 2032mm	2'8" / 813mm	35mm	25.732kg	<b>FD30</b>	<b>E M</b>	106.5mm	102mm	216mm

#### Key information

All sizes subject to standard industry tolerances

**M** = Part M - Mobility and access\*

**L** = Part L - Warmth & insulation suitable for new build\*

**L** = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

**FD30/60/120** = Certified fire door\*

**F** = Forest Stewardship Council (FSC®)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)\*

**UK** = UK Manufactured

† = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards

