



Product overview

The Sensio TrioTone™ IP65 Fire Rated Down Light offers a complete range of features all from one fitting.

It features TrioTone™ technology, which allows the light source to be changed between cool white, natural white and warm white with the press of a button. It is also fully dimmable from most standard dimmers (trailing or leading edge).

For ease of use and installation, the product comes equipped with a Power In & Out connector block. There is also no need for a driver/transformer, as the product wires straight into the mains supply.

The product is suitable for use inside and outside due to its IP65 rating, and it is also fire rated and fully compliant with all current UK building regulations.

Note: The LED lamp is integrated into the product and cannot be replaced.

Mechanical Specification

Description	Dimension (mm)	Weight (g)	IP Rating
Trio Tone IP65 Fire Rated Down Light Dual Power 5W or 8W	85(Día) x 85	Net : 235 Gross: 275	65

Benefits

- Easy To Install (Plug & Play).
- Cost Effective Solution (Offers a complete range of features all in one fitting).
- Ideal for Kitchen, Bedroom & Bathroom (All zones).
- Energy saving

Key Features

- Luminous Efficiency : 100 Lm/W.
- Brighter than a 50W GU10 Halogen.
- Reduces SKU's –Trio tone (3000K, 4000K, 5000K).
- Fully tested to 30, 60, 90 minutes fire rating.
- Dimmable from 0-100%.
- Integrated driver.
- Super slim interchangeable bezels to provide a high end solution.
- Fully compliant with all current UK building regulations.

Technical Specification

Input Voltage	220-240Vac
Power (W)	8
Lumens	800
Colour Temperature	Switchable from 3000K, 4000K, 5000K
CRI	>80
Number of Hours	50,000 Hours
Beam Angle	48°
Dimmable	0-100 % (Leading or Trailing edge dimmers)
Fire Rating	Fully Tested 30,60 and 90 minutes
Finish	White
Dimensions(mm)	85mm (Día) x580mm
Cut Out (mm)	75mm
Temperature	-10°C to +45°C
Humidity	30% to 85% Non Condensing

Order Codes

Description	Order Code	Barcode	Carton (QTY)
Trio Tone IP65 Fire Rated Down Light	SE62299T0	5060988652214	30