



J. M. Ratcliffe



Ardenbrite™

classidur®

SOLIGNUM®

SAFETY DATA SHEET

PRIME WORKTOP OIL

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME PRIME WORKTOP OIL
 PRODUCT NO. BF7000006
 APPLICATION Water-repellent protective finish for wooden surfaces.
 SUPPLIER Blackfriar Paints Ltd
 Portobello Industrial Estate
 Birtley
 County Durham
 DH3 2RE
 +44(0)191 4106611
 +44(0)191 4113147
 blackfriar@tor-coatings.com
 CONTACT PERSON ian.mccormack@tor-coatings.com;

2 HAZARDS IDENTIFICATION

Flammable. Repeated exposure may cause skin dryness or cracking. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION N;R51/53. R10, R66.

ENVIRONMENT

The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See section 12.

PHYSICAL AND CHEMICAL HAZARDS

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

HUMAN HEALTH

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Risk of serious damage to eyes. Vapours/aerosol spray may irritate the respiratory system. Repeated exposure may cause skin dryness or cracking.

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|---------------------------------------|-----------|------------|---------|------------------------------------|
| White Spirit | 265-185-4 | 64742-82-1 | 30-60% | Xn;R65. N;R51/53. R10,R66. |
| Naptha (Petroleum) Hydrotreated Heavy | 265-150-3 | 64742-48-9 | 5-10% | Xn;R65. R10,R67,R52. |
| Silica (Quartz) / Fumed Silica | | 7631-86-9 | 1-5% | Xn;R48/20. |
| XYLENE | 215-535-7 | 1330-20-7 | 1-5% | R10 Xn;R20/21 Xi;R38 |
| BUTANOL-norm | 200-751-6 | 71-36-3 | 1-5% | R10 Xn;R22 Xi;R37/38,R41 R67 |
| ETHYL METHYL KETOXIME | 202-496-6 | 96-29-7 | < 1% | Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41 |
| Cobalt Carboxylate | 237-015-9 | 13586-82-8 | < 1% | Xn;R22. Xi;R38. N;R51/53. R43. |
| Manganese Carboxylate | | 15956-58-8 | < 1% | Xi;R38. |

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

PRIME WORKTOP OIL

GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

INHALATION

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen.

Get medical attention if any discomfort continues.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Use appropriate hand lotion to prevent defatting and cracking of skin. Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids.

Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Do not use water jet as an extinguisher, as this will spread the fire.

SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Vapours are heavier than air and may spread near ground to sources of ignition.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PRIME WORKTOP OIL

| Name | Std | TWA - 8 hrs | | STEL - 15 min | | Notes |
|---------------------------------------|-----|-------------|------------|---------------|---------------|-------|
| | | | | | | |
| BUTANOL-norm | WEL | | | 50 ppm(Sk) | 154 mg/m3(Sk) | |
| Manganese Carboxylate | OES | | 5 mg/m3 | | | |
| Naptha (Petroleum) Hydrotreated Heavy | OES | | 1000 mg/m3 | | | |
| White Spirit | OES | | 600 mg/m3 | | | |
| XYLENE | WEL | 50 ppm | 220 mg/m3 | 100 ppm | 441 mg/m3 | Sk |

WEL = Workplace Exposure Limit.
 Sk = Can be absorbed through skin.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.
 All handling to take place in well-ventilated area.

RESPIRATORY EQUIPMENT

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Wear mask supplied with: Gas cartridge suitable for organic substances.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. Use protective gloves made of: Neoprene. Nitrile. Rubber (natural, latex).

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-------------------------------|----------------------------|-------------------------------|------------------|
| APPEARANCE | Liquid | | |
| COLOUR | Amber | | |
| ODOUR | Characteristic Hydrocarbon | | |
| SOLUBILITY | Immiscible with water | | |
| RELATIVE DENSITY | 0.90 Approx. @20°C. | VAPOUR DENSITY (air=1) | Heavier than air |
| FLASH POINT (°C) | 37°C. CC (Closed cup). | FLAMMABILITY LIMIT - LOWER(%) | 0.6 |
| FLAMMABILITY LIMIT - UPPER(%) | 8.0 | | |

10 STABILITY AND REACTIVITY

STABILITY

No particular stability concerns.

PRIME WORKTOP OIL**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION**GENERAL INFORMATION**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Gas or vapour is harmful on prolonged exposure or in high concentrations.

INGESTION

Gastrointestinal symptoms, including upset stomach. Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin. May be absorbed through the skin.

EYE CONTACT

Irritation of eyes and mucous membranes.

| | |
|----------------------|---------------------------------------|
| Name | White Spirit |
| Toxic Dose 1 - LD 50 | >5000 mg/kg (oral rat) |
| Name | Naptha (Petroleum) Hydrotreated Heavy |
| Toxic Dose 1 - LD 50 | 5000 mg/kg (oral rat) |

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

| | |
|--|---------------------------------------|
| Name | White Spirit |
| LC 50, 96 Hrs, FISH mg/l | 10 |
| Mobility | |
| The product is immiscible with water and will spread on the water surface. | |
| Bioaccumulation potential | |
| The product contains potentially bioaccumulating substances. | |
| Name | Naptha (Petroleum) Hydrotreated Heavy |
| LC 50, 96 Hrs, FISH mg/l | 100 |
| Mobility | |
| The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. | |
| Degradability | |
| The product is biodegradable. | |
| Acute Fish Toxicity | |
| Not considered toxic to fish. | |

13 DISPOSAL CONSIDERATIONS**GENERAL INFORMATION**

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Absorb in vermiculite or dry sand, dispose in licensed hazardous waste.

14 TRANSPORT INFORMATION

PRIME WORKTOP OIL



| | | | |
|----------------------|----------------------|-------------------------|-----------------------------|
| UK ROAD CLASS | 3 | | |
| PROPER SHIPPING NAME | PAINT (White Spirit) | | |
| UN NO. ROAD | 1263 | UK ROAD PACK GR. | III |
| ADR CLASS NO. | 3 | ADR CLASS | Class 3: Flammable liquids. |
| ADR PACK GROUP | III | TUNNEL RESTRICTION CODE | (D/E) |
| HAZARD No. (ADR) | 30 | ADR LABEL NO. | 3 |
| HAZCHEM CODE | +3YE | CEFIC TEC(R) NO. | 30GF1-III, 30GF1-sp |
| RID CLASS NO. | 3 | RID PACK GROUP | III |
| UN NO. SEA | 1263 | IMDG CLASS | 3 |
| IMDG PAGE NO. | 3 | IMDG PACK GR. | III |
| EMS | F-E, S-E | MFAG | See Guide |
| UN NO. AIR | 1263 | AIR CLASS | 3 |
| AIR PACK GR. | III | | |

15 REGULATORY INFORMATION

LABELLING



Dangerous for the environment

RISK PHRASES

| | |
|--------|---|
| R10 | Flammable. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R66 | Repeated exposure may cause skin dryness or cracking. |

SAFETY PHRASES

| | |
|--------|--|
| S2 | Keep out of the reach of children |
| S29/56 | Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. |
| S37 | Wear suitable gloves. |
| S46 | If swallowed, seek medical advice immediately and show this container or label. |
| S51 | Use only in well-ventilated areas. |
| S61 | Avoid release to the environment. Refer to special instructions/safety data sheets. |
| P14 | Contains Cobalt Carboxylate, ETHYL METHYL KETOXIME. May produce an allergic reaction. |

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40)

PRIME WORKTOP OIL

16 OTHER INFORMATION

INFORMATION SOURCES

Croner's Emergency Spillage Guide Croner's Emergency First Aid Guide Croner's Substances Hazardous to Health

REVISION COMMENTS

Corrected Product Transport information.

ISSUED BY

D Charles

REVISION DATE 17/05/2010

REV. NO./REPL. SDS GENERATED 3

SDS NO. 16154

SAFETY DATA SHEET STATUS

Approved.

DATE 17/05/2010

RISK PHRASES IN FULL

| | |
|--------|---|
| R10 | Flammable. |
| R20/21 | Harmful by inhalation and in contact with skin. |
| R21 | Harmful in contact with skin. |
| R22 | Harmful if swallowed. |
| R37/38 | Irritating to respiratory system and skin. |
| R38 | Irritating to skin. |
| R40 | Limited evidence of a carcinogenic effect. |
| R41 | Risk of serious damage to eyes. |
| R43 | May cause sensitisation by skin contact. |
| R48/20 | Harmful: danger of serious damage to health by prolonged exposure through inhalation. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R52 | Harmful to aquatic organisms. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R67 | Vapours may cause drowsiness and dizziness. |

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.