

COSHH SAFETY DATA SHEET

PRODUCT NAME: NOVIA FOIL TAPE

MATERIAL PRODUCT IDENTIFICATION

PRODUCT DESCRIPTION: Aluminium foil tape coated with a long lasting resistant acrylic adhesive on one side, lined with a release paper to protect the adhesive face.

COMPONENTS: High Performance 'Class 0 Rated' 30 Micron Aluminium Foil Tape

HAZARDS IDENTIFICATION

PHYSICAL AND CHEMICAL HAZARDS / FIRE AND EXPLOSION HAZARDS:

Non hazardous.

FIRST AID MEASURES

INHALATION:

o Not applicable.

SKIN CONTACT:

oFirst aid is normally not required.

EYE CONTACT:

oFlush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

INGESTION:

o If ingested, consult doctor.

FIRE -FIGHTING MEASURES

FIRE-FIGHTING PROCEDURES:

- o Use water spray to cool fire exposed surfaces and to protect personnel.
- o Block the supply to the fire.
- o Extinguish the fire by cooling with water spray.

SPECIAL FIRE PRECAUTIONS:

- o Water, dry powder, carbon dioxide, or foam may be used as extinguishers.
- o See Sections 4 "First Aid Measures" and 10 "Stability and Reactivity"

HAZARDOUS COMBUSTION PRODUCTS:

o No unusual materials

ACCIDENTAL RELEASE MEASURES

LAND SPILL:

- o Sweep up spilled material and place in suitable containers for recycle or disposal.
- o Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- o See Sections "First Aid Measures" and "Stability and Reactivity"

WATER SPILL:

- o Stop source if possible to do so without hazard. Advise authorities of possible floating substances, if material enters watercourses or sewers. Confine if possible.
- o Skim from surface.
- o Consult an expert on disposal of any recovered material and ensure conformity to local disposal regulations.
- o See Sections "First Aid Measures" and "Stability and Reactivity".

HANDLING AND STORAGE

STORAGE TEMPERATURE (Deg C): Ambient

TRANSPORT TEMPERATURE (Deg C): Ambient

LOADING / UNLOADING TEMPERATURE (Deg C): Ambient

VISCOSITY (cSt): Not Applicable

STORAGE / TRANSPORT PRESSURE (kPa): Atmospheric

ELECTROSTATIC ACCUMULATION HAZARD: None from product, slight static charge may be developed from the removal of the release paper, if relevant use appropriate grounding procedures.

USUAL SHIPPING CONTAINERS: In cardboard cartons, on wooden pallets.

MATERIALS AND COATINGS UNSUITABLE: None

STORAGE / HANDLING, GENERAL NOTES: Store in a cool, well ventilated place away from incompatible materials. Do NOT remove release liner or store cartons of product near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight.

EXPOSURE CONTROL / PERSONAL PROTECTION

ENGINEERING CONTROL MEASURES: No special requirements

PERSONAL PROTECTION: No special requirements

STABILITY AND REACTIVITY

HAZARDOUS POLYMERISATION? No

CONDITIONS TO AVOID POLYMERISATION: Not Applicable

STABILITY: Stable

CONDITIONS TO AVOID INSTABILITY: Not Applicable

MATERIALS AND CONDITIONS TO AVOID (INCOMPATIBILITY): Strong

oxidizing agents, product will be affected by organic solvents. HAZARDOUS DECOMPOSITION PRODUCTS: None

TOXICOLOGICAL INFORMATION

INHALATION: Negligible hazard at ambient temperatures.

SKIN CONTACT: Low order of toxicity.

EYE CONTACT: Slightly irritating due to solid form but composition not known to

injure eye tissue

INGESTION: Minimal toxicity.

DISPOSAL CONSIDERATIONS

Aluminium foil tape is not classified as 'notifiable waste' under the Disposal of Poisonous Wastes Act 1972, and may be disposed of by landfill or by incineration in compliance with Local Authority Control Pollution Act 1974. Material is not biodegradable.

REGULATORY INFORMATORY

CLASSIFICATION AND LABELLING ACCORDING TO EEC DIRECTIVES CLASSIFICATION/SYMBOL: Not Regulated GOVERNING DIRECTIVE: According to the EEC Directives, the product does not require classification and labeling.

NOVIA LTD, Unit 12 Heronden Road, Parkwood Industrial Estate, Maidstone, Kent. ME15 9YR Tel (01622) 678952 Fax (01622) 679025 e-mail: sales@novia.co.uk Registered Office: Star House, Star Hill, Rochester, ME1 1UX Company reg no. 3229379 VAT reg. no. GB 662 277131