## MATERIAL SAFETY DATA SHEET

### 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:Cordless Fuel CellCHEMICAL FAMILY:HydrocarbonsCHEMICAL NAME:Compressed, extremely flammable, liquified gasMANUFACTURER:INFORMATION TELEPHONE NUMBER:Paslode847-634-1900888 Forest Edge DriveEMERGENCY TELEPHONE NUMBER:Vernon Hills, Illinois 60061-3105800-424-9300 (CHEMTREC)

### 2. <u>COMPOSITION / INFORMATION ON INGREDIENTS (fuel and propellant)</u>

|                       | CAS      | CONCENTRATION |
|-----------------------|----------|---------------|
| HAZARDOUS INGREDIENTS | NUMBER   | (% by weight) |
| 1-butene (butylene)   | 106-98-9 | 25-80         |
| propene (propylene)   | 115-07-1 | 20-75         |

### **EU CLASSIFICATION:**

F+, R12 - Extremely flammable.

### EU RISK AND SAFETY PHRASES:

R12 - Extremely flammable.

S2 - Keep out of the reach of children.

S9 - Keep container in a well-ventilated place.

S16 - Keep away from sources of ignition - No smoking.

S33 - Take precautionary measures against static discharges.

### 3. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

Self-pressurized container of extremely flammable, liquified gas. Storage at temperatures above 120°F may create a fire hazard.

PRIMARY ROUTES OF ENTRY: Respiratory system, eyes and skin.

# POTENTIAL HEALTH EFFECTS

**EYE CONTACT:** Direct contact with liquefied gas can result in frostbite ("cold burn"). **SKIN CONTACT:** Exposure to expanding gas or vaporizing liquid may cause frostbite. **INGESTION:** Exposure to expanding gas or vaporizing liquid may cause frostbite to internal organs and tissue. Ingestion not anticipated since components of fuel gas and propellant are gaseous at ambient pressure and temperature.

**INHALATION:** May cause asphyxiation in high concentrations. Repeated or prolonged inhalation may cause toxic effects. See MSDS Section 11 for more information.

### 4. FIRST AID MEASURES

**EYE:** Immediately flush eyes with plenty of water. Get immediate medical attention. **SKIN:** In case of frostbite, do not remove clothes. Get immediate medical attention. **INGESTION:** Get immediate medical attention.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

#### 5. <u>FIRE FIGHTING MEASURES</u> FLASH POINT: approximately -160°F FLAMMABILITY LIMITS (% in air by volume): approximately 2 to 10 EXTINGUISHING MEDIA: dry chemical; carbon dioxide; foam; water SPECIAL FIRE FIGHTING PROCEDURES: Fuel cells may release contents if not sufficiently cooled with water spray. Isolate hazard area and evacuate unprotected personnel. Full emergency equipment with self contained breathing apparatus and full protective clothing should be worn by firefighters.

#### 6. <u>ACCIDENTAL RELEASE MEASURES</u> SPILL OR LEAK PROCEDURES: Eliminate sources of ignition. Isolate hazard area. Ventilate hazard area.

# 7. HANDLING AND STORAGE

**RECOMMENDED STORAGE TEMPERATURE:** Below 120<sup>°</sup> F **SHELF LIFE:** For maximum number of tool cycles, use before date code on fuel cell. **HANDLING AND STORAGE PRECAUTIONS:** In addition to limitations on storage temperature, fuel cells should be handled and stored so as to avoid puncture. Even after use, do not puncture fuel cell or expose fuel cell to high temperature. Do not attempt to refill the fuel cell.

### 8. EXPOSURE CONTROL/PERSONAL PROTECTION

# **EYE PROTECTION REQUIREMENTS:**

Eye protection must be worn when handling fuel cells. **SKIN PROTECTION REQUIREMENTS:** 

Gloves are recommended when handling fuel cells.

**RESPIRATORY/VENTILATION REQUIREMENTS:** 

Use in a well ventilated environment.

| EXPOSURE LIMITS:    | OSHA PEL | ACGIH |  |
|---------------------|----------|-------|--|
|                     | (ppm)    | (ppm) |  |
| 1-butene (butylene) | NE       | NE    |  |
| propene (propylene) | NE       | NE    |  |

### 9. PHYSICAL AND CHEMICAL PROPERTIES (fuel and propellant)

| liquified gas  |
|--|
| colorless  |
| faintly olefinic   |
| approximately -50°F  |
| approximately -300°F   |
| not applicable   |
| slightly   |
| approximately 0.6 for liquefied gas                            |
| 100%   |
| approximately 50 - 150 lb/in <sup>2</sup> at 70 <sup>°</sup> F |
| approximately 1.5 (air = 1)                                    |
|  |

## 10. <u>REACTIVITY</u> STABILITY: HAZARDOUS POLYMERIZATION: INCOMPATIBILITIES: DECOMPOSITION PRODUCTS:

Product is stable. Will not occur.

Oxidizing agents, halogens and acids. Thermal decomposition or burning may

produce carbon monoxide or carbon dioxide from fuel gas combustion.

## 11. TOXICOLOGICAL INFORMATION

**ACUTE INHALATION:** Low toxicity - LC50 > 5 mg/L (rat). Components of fuel cell gases and propellant are simple asphyxiants. Exposure to high concentrations of propylene has been associated with irregular heartbeat.

**CHRONIC INHALATION:** No significant effects have been demonstrated for any components except propylene. Chronic exposure to propylene has been associated with liver damage.

**ACUTE EYE OR SKIN CONTACT:** Frostbite ("cold burn") can result from exposure to expanding gas or vaporizing liquid. Components of fuel cell gas and propellant at ambient pressure and temperature produce little or no irritation.

**CHRONIC EYE OR SKIN CONTACT:** No significant effects have been demonstrated for components of fuel cell gas and propellant at ambient pressure and temperature. **CARCINOGENCITY:** No components of fuel cell gas or propellant are classified as carcinogens by IARC, NTP or OSHA.

### 12. ECOLOGICAL INFORMATION

Ecotoxicological and environmental fate data have not been determined specifically for this product. Information is based on International Uniform Chemical Information Database (IUCLID) entries for components of fuel cell gas and propellant.

**ECOTOXICOLOGIAL INFORMATION:** Anaesthetic to animals and insects at high concentrations. Not expected to pose hazards to aquatic life. Not inhibitory to plant growth at ambient concentrations. Bioaccumulation is not expected.

**ENVIRONMENTAL FATE INFORMATION:** Volatilization is expected to be primary fate process. Components of fuel cell gas and propellant have photochemical reactivity.

### 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHOD:** Waste must be disposed of in accordance with federal, state and local environmental regulations. See RCRA discussion in MSDS Section 15.

#### 14. <u>TRANSPORT INFORMATION</u> U.S. DOT INFORMATION (ground shipment):

**PROPER SHIPPING NAME:** Consumer Commodity HAZARD CLASS: ORM-D **PRODUCT RQ (lbs):** none UN NUMBER: LABEL: none none IMDG INFORMATION (vessel shipment): **PROPER SHIPPING NAME:** Aerosols, LTD QTY HAZARD CLASS: 2.1 **PRODUCT RQ (lbs):** none UN NUMBER: UN1950 LABEL: Flammable gas

| 15. | REGULATORY INFORMATION<br>TSCA STATUS: All components are included in the TSCA Chemical Inventory.<br>CERCLA REPORTABLE QUANTITY: none<br>SARA TITLE III:   |   |        |                                      |  |  |  |
|-----|---|---|--------|--------------------------------------|--|--|--|
|     | SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES: none<br>SECTION 311/312 HAZARD CATEGORIES:  |   |        |                                      |  |  |  |
|     | Acute Health  | yes   |        |                                      |  |  |  |
|     | Chronic Health  | yes   |        |                                      |  |  |  |
|     | Fire  | yes   |        |                                      |  |  |  |
|     | Reactive  | no  |        |                                      |  |  |  |
|     | Sudden Release of Pressu  |   |        |                                      |  |  |  |
|     | SECTION 313 TOXIC CHEMICA   | ,   | lene)  | CAS No. 115-07-1<br>20-75% by weight |  |  |  |
|     | RCRA STATUS: If discarded in its purchased form, this product may be classified as D001 (ignitable) hazardous waste. Even after use, the fuel cell remains pressurized an extremely flammable propellant and may retain these hazardous waste characteristics. Waste generators must consider federal, state and local hazardous waste regulations to determine a proper disposal method based on their status as a conditionally exempt, small quantity or large quantity generator.   CANADIAN STATUS: All components listed on Domestic Substances List (DSL).   EUROPEAN UNION: All components listed on European Inventory of Existing Commercial Chemical Substances (EINECS):   Component EINECS No.   1-butene 203-449-2   propene 204-062-1   STATE REGULATORY INFORMATION: No component of fuel gas or propellant is included on California Proposition 65 lists as a carcinogen or reproductive toxin. |   |        |                                      |  |  |  |
| 16. | OTHER INFORMATION   |   |        |                                      |  |  |  |
|     | HMIS CLASSIFICATION:  | Health  | 1      |                                      |  |  |  |
|     | * To be determined by user  | Flammability  | 4      |                                      |  |  |  |
|     | under specific conditions.  | Reactivity<br>PPE   | 0<br>* |                                      |  |  |  |
|     | REASON FOR ISSUE:<br>PREPARED BY:<br>ISSUE DATE:<br>SUPERCEDES VERSION DATED:   | Added vessel information in Section 14<br>Ken Brown, CHMM<br>9/14/10<br>7/29/10 |        |                                      |  |  |  |

The information contained in this material safety data sheet is provided without warranty, expressed or implied, except that it is accurate to the best knowledge of Paslode. The data on this sheet relate only to the Cordless Fuel Cell. Paslode assumes no legal responsibility for use or reliance upon these data.