

90cm Chimney Hood



| Technical Information | |
|---|---------------------------------------|
| Appliance energy rating | D |
| Extraction rate | 440 m ³ /h |
| Extraction rate ltr/s | 122.2 L/s |
| Number of fan speeds | 3 |
| Number of lights x Light wattage (per bulb) | 2 x 5 W |
| Light type | LED |
| Number of Grease Filters | 3 x Washable Filters |
| Carbon Filter Required | Required for Recirculation - Included |
| Remote control | N/A |
| Outlet spigot diameter | 150mm |
| Ducting kit diameter | 125mm |
| Air extraction rate ducting - speed range | 240-440 m ³ /h |
| Air extraction rate recirculation - speed range | 140-235 m ³ /h |
| Noise level ducting | 55-69 dB |
| Noise level recirculation | 60-72 dB |
| Electrical supply voltage / Frequency | 230 V / 50 Hz |
| Amperage required | 3 A |
| Mains lead length | 1 m |
| Approval directives | CE |
| Guarantee | 2 Year Manufacturer's Guarantee |

| Dimensions & packaging | |
|---------------------------|-------------------------------|
| Product dimensions metric | H735-1010mm x W898mm x D490mm |
| Chimney dimensions | W210mm x D205mm |
| Product weight | 15.67kg |
| Product packed dimension | H550mm x W968mm x D382mm |
| Product packed weight | 19kg |

Accessories

Additional information

Ducting kit sold separately